

MFA 633 - 1 Input - UHF - Group mast amplifier

340633



MFA 633 - UHF - mast amplifier

- F-connectors on all in- and outputs
- 4-terminal waterproof masthousing
- RF shielded & CE approved (EN 50083)

Technical Specifications

ORDER INFORMATION

EAN Number 5702663406339

CHARACTERISTICS

Max. Output level @ 60 dB IMD 105 dB μ V

FREQUENCY

Input 1 - frequency 470...862 MHz

Input 1 - band UHF

Input 1 - channels 21...69

GAIN

Input 1 - gain 24...34 dB

Input 1 - noise figure 2.5 dB

RETURN LOSS

Return Loss 10 dB

OPERATIONAL

DC Operating voltage 12...24 VDC

DC Current consumption (typ.) 60 mA

CONNECTORS

Number of inputs 1

Number of outputs 1

Connector Type F-female

MECHANICAL

Height (mm) 115 mm

Depth (mm) 60 mm

Width (mm) 117 mm

Packaging Volume 0,001 m³

Net Weight 0,300 kg

Tara Weight 0,000 kg

Total Weight 0,300 kg

Packaging Height 0,060 m

01-06-2016

Triax - MFA 633 - 1 Input - UHF - Group mast amplifier

Packaging Width	0,110 m
Packaging Depth	0,120 m