

TBF 2IP 2MP IPCam fix lens PoE
301092



Features and Benefits

TBF 2IP

- 1/2.8" 2.0 Mega progressive scan CMOS
- H.264 1080p Real time recording
- 2D/3D DNR, DWDR, Anti-fog
- Long Distance, No delay
- Support PoE
- Support reset Button IR Array
- Support ONVIF
- Support intrusion detection
- Dual-Stream
- IP66
- TRIAX P2P mobile App

Technical Specifications

ORDER INFORMATION

EAN Number 5702663010925

CHARACTERISTICS

Image Sensor	1/2.8" 2.0 Mega progressive scan CMOS
Video resolution	1920 x 1080 Pixel
Shutter speed	Auto (1/10s ~ 1/10000s Adjustable) sec.
Lens	3.6mm
Day & Night	Auto/Color/B&W (IR_CUT)
Digital Noise Reduction	2D/3D
Wide Dynamic Range	Digital WDR
Image Settings	Sharpness, Brightness, Saturation, Contrast Adjustable

ELECTRICAL

IR Distance 30 m

OPERATIONAL

Compression Format	H.264
Network Protocols	TCP/IP, UDP, HTTP, IGMP, ICMP, DHCP, RTP/RTSP, DNS, DDNS, FTP, NTP, PPPOE, UPNP, SMTP, SNMP
Interface	RJ45 10M/100M adaptive Ethernet interface
Operating temperature range	-10 - +60 °C
Humidity - operating	10 - 90 %

Power Consumption (typ.)	5.5 Max W
DC Operating voltage	12 VDC
Protocols	Support ONVIF and CGI protocol
Weather Proof Rating	IP66

MECHANICAL

Lens Mount	M12
Length (mm)	155 mm
Diameter	69 mm
Height (mm)	69 mm
Weight (g)	530 g
Packaging Volume	0,002 m3
Net Weight	0,650 kg
Tara Weight	0,200 kg
Total Weight	0,850 kg
Packaging Height	0,210 m
Packaging Width	0,110 m
Packaging Depth	0,100 m