

TDV 2IP 2MP IPCam2.8-12mmVFPoE
301098



Features and Benefits

TDV 2IP

- 1/2.8" 2.0 Mega progressive scan
- H.264 1080p Real time recording
- 2D/3D DNR, DWDR, Anti-fog
- Support PoE, Support reset Button
- Support ONVIF
- Support intrusion detection
- Dual-Stream
- IP66
- TRIAX P2P mobile App

Technical Specifications

ORDER INFORMATION

EAN Number 5702663010987

CHARACTERISTICS

Image Sensor	1/2.8" 2.0 MP progressive scan CMOS
Video resolution	1920 x 1080 Pixel
Shutter speed	Auto (1/10s ~ 1/10000s Adjustable) sec.
Lens	2.8 to 12 mm varifocal lens
Day & Night	Auto/Color/B&W (IR_CUT)
Digital Noise Reduction	2D/3D
Wide Dynamic Range	Digital WDR
Image Settings	Sharpness, Brightness, Saturation, Contrast Adjustable

ELECTRICAL

IR Distance 30 m

OPERATIONAL

Compression Format	H.264 / MJPEG
Network Protocols	TCP/IP, UDP, HTTP, IGMP, ICMP, DHCP, RTP/RTSP, DNS, DDNS, FTP, NTP, PPPOE, UPNP, SMTP, SNMP
Interface	RJ45 10M/100M adaptive Ethernet interface
Operating temperature range	-10 - +60 °C
Humidity - operating	10 - 90 %
Power Consumption (typ.)	6,5 Max W
DC Operating voltage	12 VDC
Protocols	Support ONVIF and CGI protocol

Weather Proof Rating IP66

MECHANICAL

Length (mm)	140 mm
Diameter	126,7 mm
Weight (g)	975 g
Packaging Volume	0,008 m3
Net Weight	1,250 kg
Tara Weight	0,200 kg
Total Weight	1,450 kg
Packaging Height	0,210 m
Packaging Width	0,205 m
Packaging Depth	0,180 m