
Adaptor SMA Jack-N Plug





Specifications:

Frequency	: DC-11GHz		
Bodies	: Brass per JIS-C3604		
Centre Contact	: Beryllium copper per ASTM B196 UNS C17300		
Insulation	: PTFE per ASTM D1457 and ASTM D1710		
Connector interface per MIL-STD-348A			
Part to be clean and free of burrs			



Dimensions : Millimetres (Inches)

Specification Table

No.	Description	Material	Finish
1	Shell	Brass	Nickel 100µ Inches Min.
2	Gasket	Silicone	Red
3	Body I	Brass	Nickel 100µ Inches Min.
4	Washer	DIASS	None
5	Centre Contact	Beryllium Copper	Gold
6	Body II	Brass	Nickel 100µ Inches Min.
7	Insulation	PTFE	None

Part Number Table

Description	Part Number
Adapter, N Plug, SMA Jack, 50 Ω	19-34-2

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of use of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com

